

# Adapting Nitrogen Management to the Increasing Climatic Uncertainty

Dumont B.<sup>1,2,\*</sup>, Basso B.<sup>2</sup>, Destain J.-P.<sup>1</sup>, Bodson B.<sup>1</sup> & Destain M.-F.<sup>1</sup>

<sup>1</sup> Gembloux Agro-Bio Tech, University of Liege, Gembloux, Belgium

<sup>2</sup> Department of Geological Sciences, Michigan State University, Lansing, MI, USA

\* Passage des Déportés, 2, 5030, Gembloux, Belgium, @:benjamin.dumont@ulg.ac.be, tel: +32(0)81/62.21.64

*ASABE : 250 words*

With abbreviated return times of extreme events, management of nitrogen (N) will become even more a priority issue. The decision-making process of N application is complex because the N optimal rate varies spatially and temporally and the impact of a decision is delayed in time from its application. The objective of this paper is to develop a decision support system (DSS) to optimise N management in an ecosystem perspective, including crop production and environmental objectives.

Winter wheat response to N was analysed between 2008 and 2014 on Luvisols, in temperate climate (Belgium). The usual Belgian practice consists to apply 60-60-60kgN.ha<sup>-1</sup> respectively at tiller, stem extension and flag-leaf stages. By using the STICS model, the effect of variable N rates on crop growth and N available for leaching (NAL) were computed. 300 stochastic weather time-series were derived from LARS-WG for actual and future climatic conditions. The farmer's marginal net revenues (MNR) were computed as function of N costs and wheat selling prices. For each climatic probability level, the ratio  $R = \text{MNR}/\text{NAL}$  was estimated in function of the N rates. To minimize the risks, the DSS considered the curve  $R=f(N)$  corresponding to the probability level of 75%. The best N rate was the maximum value of this curve.

Results indicated that, under actual conditions, the N rates applied at flag-leaf could, at least 3 years out of 4, be decreased by 10 to 30kgN.ha<sup>-1</sup>. Under A1B scenarios, the optimal N practice could be decreased between 60-60-0kgN.ha<sup>-1</sup> and 60-60-30kgN.ha<sup>-1</sup>.