

# LIFE CYCLE ASSESSMENT OF BIOBASED CHEMICAL BUILDING BLOCKS MADE FROM EUROPEAN WASTE STREAMS



www.renew-network.eu



# S. GROSLAMBERT & A. LÉONARD

University of Liège (BE) – Department of Chemical Engineering – PEPs

www.chimapp.ulg.ac.be - s.groslambert@ulg.ac.be



# Introduction

Many drivers exist to persuade EU businesses to embrace the opportunities of the circular economy. However, the challenges faced by companies, particularly among SME's, in the drive for resource efficiency include access to funding, knowledge and capability, and ability to implement cost-effective technological solutions. It was these factors that inspired the creation of the ReNEW network. **ReNEW, 'Resource innovation Network for European Waste'**, is a €5 million project funded by the Interreg IVB North West Europe scheme aiming to increase cooperation between research and business endeavours to create value from waste by optimising novel technologies for extracting materials from waste and their reuse in the supply chain. ReNEW also aims to inform local, national and European policy makers, and to share transnational best practice and improve specific support to meet the innovation needs of the waste sector.

Within the frame of this project, several technologies are investigated by partners to improve the valorisation of organic wastes in chemicals such as the production of furfural (C<sub>5</sub>H<sub>4</sub>O<sub>2</sub> - CAS 98-01-1) by the chemical hydrolysis of contaminated/hazardous woody biomass.

# **Materials and Methods**

### Goal definition

The aim of this study is to assess the environmental impacts of the production of furfural from (contaminated) woody biomass hydrolysed with formic acid.

#### Methods

- Life Cycle Assessment methodology, ILDC 2011 [1]
- ReCiPe 2008 (European hierarchist version 1.11, update 2014) [2]
- This study is done in accordance with the ISO standards 14040 [3] and 14044 [4].
- SimaPro 8.0.4 software (PRé-Consultant)
- Ecoinvent 3.1 database [5]

#### The functional unit is 1 kg of furfural.

A model for the process is developed by the University of Limerick (IE) (project partner).

The LCA is based on results obtained with Aspen-Hysis simulation software (Figure 1)


(hypothesis: perfect energetic integration – complete heat recovery).

**Inventory:** included: chemicals, energy (heat supply/recovery, electricity), Ireland electricity mix (86.31% fossil fuels), wastewater treatment excluded: wood grinding, reactors and columns vessels, pumps and other material

#### 19.73 kg/h O2 14.42 kh/h CO2 46.56 kh/h DM (cellulose) 100 kg/h DM wood waste 16.36 kh/h DM (91.6% DM) 10-Dry Lignin 1-Biomass 50 kg/h 12-Diluted U1 11-Diluted 2-Hydrogen peroxide 4-Pulp+Liquor 6-Liquor Evaporation Liquor liquor Pretreatment Separation Separation 3-Fresh Formic Acid 7-Washing 78 kg/h 20a-FA/water 9-Diluted FA 14-Concentrated liquor 9a-Water\* 3355.3 kg/h 3a-Recovered 20c-FA/water Formic acid 13-Water/FA Formic acid | 20-FA/Water 19-Waste water Recovery 18-FA/Water 3470.70 kg/h U6 15-Furfural/Water/FA U5 17-Furfural **Furfural** Reaction Recovery 16-Waste/by-products

Figure 1. Furfural production from woody biomass

# **Results and Discussion**



U7-Formic acid recovery
 U6b-Distillation2

 furfural
 U6a-Distillation1
 solid byproducts
 U5-Reaction

 U4-Evaporation
 HC liquor
 U3-Separation lignin
 U2-Separation cellulose
 U1-Pretreatment




Figure 2: Relative contribution of each step of the production of 1 kg of furfural

- Most impacting steps: (Figure 2)
  - Unit 1: Pretreatment: use of formic acid and hydrogen peroxide
- Negative impacts: system boundaries expansion
  - Unit 2: separation of cellulose: avoided cellulose fibres
  - Unit 3: separation of lignin: heat from burnt lignin
  - Unit 6a distillation n°1: solid by-products: heat (burnt)




Figure 3: Normalisation of impact of 1 kg of furfural

# **Most impacted categories:** (Figure 3)

- Ecotoxicity (fresh and marine water)
- Eutrophication (fresh and marine water)
- Human toxicity
- Fossil fuel depletion (cf. IE mix)

# Conclusions

A preliminary life cycle assessment of the production of furfural from (contaminated/hazardous) woody biomass is done. The most impacting part is chemicals consumption, especially formic acid. Major improvements have to be done to limit the environmental impacts on water (ecotoxicity, eutrophication).

The model has to be enhanced but it gives ways to optimise furfural production from lignocellulosic wastes, such as the use of biobased formic acid, and water recycling. The results will be compared to the business-as-usual route to produce furfural (to be calculated - data not available in common databases or literature).

## References

- [1] European Commission Joint Research Centre Institute for Environment and Sustainability (2010). International Reference Life Cycle Data System (ILCD) Handbook General guide for Life Cycle Assessment Detailed guidance. First edition March 2010. EUR 24708 EN. Luxembourg., Publications Office of the European Union
- [2] Goedkoop, M., et al., ReCiPe 2008 A life cycle impact assessment method which comprises harmonised category indicators at the midpoint and the endpoint level, Ruimte en Milieu, Editor 2009
- [3] ISO 14040:2006 Environmental management Life cycle assessment Principles and framework
- [4] ISO 14044:2006 Environmental management Life cycle assessment Requirements and guidelines [5] Ecoinvent Centre, The life cycle inventory data version 3.01, 2014. Swiss Center for Life Cycle Inventories. http://ecoinvent.ch/
  - SETAC Europe 25<sup>th</sup> Annual Meeting, Barcelona (SP), 3-7 May 2014